

Tel: 770.350.1659 Fax: 770.350.1658 www.arauco-na.com

## FLAME SPREAD PERFORMANCE OF COMPOSITE WOOD PANELS AND FINISHES

Unless otherwise stated, Arauco North America particleboard or MDF in industrial or laminated 1 forms are not certified for a specific flame spread rating.

Untreated particleboard and MDF have been tested for flame spread by a number of different manufacturers and the results met the Class III or C rating. The Department of Housing and Urban Development (HUD) in their Manufactured Home Construction and Safety Standards (Section 3280.203) accepts particleboard 3/8 inch and thicker as having a flame spread rating of 76 to 200 for general use in mobile homes.

The American Wood Council (AWC) of the American Forest and Paper Association (AF&PA) has published information in their "Design for Code Acceptance" series (DCA1) relating to Flame Spread Performance of Wood Products. The document can be found at www.awc.org. Table 1 in that document places particleboard and MDF in the Class III or C rating, Likewise, Table 2 in that document places factory finished products (i.e. printed or with overlays) containing untreated particleboard and MDF substrates in the Class III or C flame spread rating.

Smoke data specific to every product is currently not available; however other manufacturers have found typical values of 100-200 for smoke developed. The AF&PA document states that "a smoke developed index was measured for some of the wood products listed in Tables 1 and 2". None of the products tested exceeded 450, a limiting value commonly used in building code regulations.

Arauco North America particleboard and MDF treated with fire-retardant<sup>3</sup> (FR) additives are certified by

Underwriters Laboratories to have a Class A or Class I flame spread rating<sup>4</sup>. In addition, TFL (melamine) applied to Arauco North America's fire-rated particleboard or MDF substrates at the St. Stephen, NB or Albany, OR laminating facilities are classified by Underwriters Laboratories to have a Class A or Class I flame spread rating<sup>4</sup>.

Mike Luepkes Business Technical Director Phone: 705-989-6202 mike.luepkes@arauco-na.com http://www.arauco-na.com

R2016-01-13

Arauco North America is a trade name used by Flakeboard Company Limited, Flakeboard America Limited, Arauco Panels USA LLC, and other North America affiliates. This letter is intended for customers of Flakeboard Company Limited, Flakeboard America Limited, and Arauco Panels USA LLC, each of which is an independent company and is not liable or responsible for acts or obligations of its affiliates.

<sup>1</sup> TFM (thermally fused melamine), decorative paper overlay, wet coated- i.e./ Rezcote-paint or direct print 2 Without a fire-retardant additive

<sup>3</sup> Trade names: Duraflake® FR, Premier FR®, VESTA FR Particleboard, VESTA FR MDF

<sup>4</sup> UL 723 Test for Surface Burning Characteristics of Building Materials

CAN/ULC - S102 Test for Surface Burning Characteristics of Building Materials